

**KOMATSU FOREST**

Harvesters



Machine	Tyre size / PR	Tread pattern						Inflation pressure				Max inflation and track pressure			
								Front		Rear		kPa	p.s.i.		
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.				
<b>901</b> 4 wheels	600/65-34/20							*)Front, Rear		320	46	320	46	360	52
	600/65R34							Front, Rear		320	46	320	46	400	58
	710/55R34							Front, Rear		320	46	320	46	400	58
	700/55-34/20							*)Front, Rear		320	46	320	46	360	52
<b>901</b> 6 wheels	600/50R24.5							Front		550	80			550	80
	650/45R24.5							Front		550	80			550	80
	710/40-24.5/20	Front	Front	Front						550	80			550	80
	600/65R34							Rear				300	44	400	58
	600/65-34/20								*)Rear			300	44	360	52
	710/55R34							Rear				300	44	400	58
	700/55-34/20								*)Rear			300	44	360	52
<b>911</b> 4 wheels	600/65-34/20								*)Front, Rear	320	46	320	46	360	52
	600/65R34							Front, Rear		320	46	320	46	400	58
	710/55R34							Front, Rear		320	46	320	46	400	58
	700/55-34/20								*)Front, Rear	320	46	320	46	360	52
<b>911</b> 6 wheels	600/55R26.5							Front		460	67			550	80
	600/55-26.5/20	Front	Front	Front, *)Front					*)Front	460	67			550	80
	710/45R26.5							Front		460	67			550	80
	710/45-26.5/16							Front		460	67			460	67
	710/45-26.5/20	Front	Front	Front, *)Front					*)Front	460	67			550	80
	710/45-26.5/24	Front						Front		460	67			600	87
	800/40-26.5/20	Front	Front	Front						460	67			550	80
	600/65R34							Rear				300	44	400	58
	600/65-34/20								*)Rear			300	44	360	52
	710/55R34							Rear				300	44	400	58
700/55-34/20								*)Rear			300	44	360	52	
<b>931</b> 6 wheels	600/55R26.5							Front		500	73			550	80
	600/55-26.5/20	Front	Front	Front, *)Front					*)Front	500	73			550	80
	710/45R26.5							Front		500	73			550	80
	710/45-26.5/20	Front	Front	Front, *)Front					*)Front	500	73			550	80
	710/45-26.5/24	Front						Front		500	73			600	87
	800/40-26.5/20	Front	Front	Front						500	73			550	80
	600/65R34							Rear				300	44	400	58
	600/65-34/20								*)Rear			300	44	360	52
	710/55R34							Rear				300	44	400	58
700/55-34/20								*)Rear			300	44	360	52	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.










Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

**KOMATSU FOREST**

Harvesters



Machine	Tyre size / PR	Tread pattern						Inflation pressure				Max inflation and track pressure	
								Front 		Rear			
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>941.1</b> 6 wheels	650/65-26.5/20					Front	Front	500	73			550	80
	750/55-26.5/20			Front, *)Front			Front, *)Front	500	73			550	80
	750/55-26.5/24	Front	Front					500	73			600	87
	780/55-26.5/20			Front				500	73			550	80
	800/50R26.5				Front			500	73			550	80
	700/70-34/16						Rear			260	38	260	38
	700/70-34/20						*)Rear			300	44	360	52
	710/70R34					Rear				300	44	400	58
<b>951</b> 6 wheels	710/55-28.5/24	Front	Front					500	73			600	87
	780/50-28.5/24	Front	Front					500	73			600	87
	710/70R34					Rear				300	44	400	58

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.











Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

**KOMATSU FOREST**

Forwarders



Machine	Tyre size / PR	Tread pattern						Inflation pressure				 Max inflation and track pressure	
								Front 		Rear			
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>830.3</b> 8 wheels	600/50-22.5/16					Front,Rear	Front,Rear	350	51	430	62	430	62
	600/50-22.5/20						Front,Rear	350	51	500	73	550	80
	710/40-22.5/16			Front, Rear			Front,Rear	350	51	400	58	400	58
<b>840TX</b> 8 wheels	600/50R24.5					Front,Rear		400	58	550	80	550	80
	650/45R24.5					Front,Rear		400	58	550	80	550	80
	710/40-24.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	550	80	550	80
<b>835</b> 8 wheels	600/50R24.5					Front,Rear		400	58	550	80	550	80
	650/45R24.5					Front,Rear		400	58	550	80	550	80
	710/40-24.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	550	80	550	80
<b>840.4</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear			*)Front,Rear	350	51	550	80	550	80
	600/55R26.5				Front, Rear			350	51	550	80	550	80
	710/45R26.5				Front, Rear			350	51	500	73	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear			*)Front,Rear	350	51	500	73	550	80
	710/45-26.5/24	Front, Rear		Front, Rear				350	51	500	73	600	87
	800/40-26.5/20	Front, Rear	Front,Rear	Front, Rear				350	51	500	73	550	80
<b>840.4</b> 6 wheels	600/55-26.5/20	Rear	Rear	Rear, *)Rear			*)Rear			550	80	550	80
	600/55R26.5				Rear					550	80	550	80
	710/45R26.5				Rear					500	73	550	80
	710/45-26.5/20	Rear	Rear	Rear, *)Rear			*)Rear			500	73	550	80
	710/45-26.5/24	Rear		Rear						500	73	600	87
	800/40-26.5/20	Rear	Rear	Rear						500	73	550	80
	600/65R34				Front			320	46			400	58
	600/65-34/20						*)Front	320	46			360	52
710/55R34				Front			320	46			400	58	
700/55-34/20						*)Front	320	46			360	52	
<b>845</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear			*)Front,Rear	350	51	550	80	550	80
	600/55R26.5				Front, Rear			350	51	550	80	550	80
	710/45R26.5				Front, Rear			350	51	500	73	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear			*)Front,Rear	350	51	500	73	550	80
	710/45-26.5/24	Front, Rear		Front, Rear				350	51	500	73	600	87
800/40-26.5/20	Front, Rear	Front,Rear	Front, Rear				350	51	500	73	550	80	
<b>855.1</b> 8 wheels	710/45R26.5				Front, Rear			350	51	500	73	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear			*)Front,Rear	350	51	500	73	550	80
	710/45-26.5/24	Front, Rear		Front, Rear				350	51	500	73	600	87
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear				350	51	500	73	550	80
<b>855.1</b> 6 wheels	710/45R26.5				Rear					500	73	550	80
	710/45-26.5/20	Rear	Rear	Rear, *)Rear			*)Rear			500	73	550	80
	710/45-26.5/24	Rear		Rear						500	73	600	87
	800/40-26.5/20	Rear	Rear	Rear						500	73	550	80
	600/65R34				Front			340	49			400	58
	600/65-34/20						*)Front	340	49			360	52
	710/55R34				Front			340	49			400	58
700/55-34/20						*)Front	340	49			360	52	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.











Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

**KOMATSU FOREST**

Forwarders



Machine	Tyre size / PR	Tread pattern						Inflation pressure				 Max inflation and track pressure	
								Front 		Rear			
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>860.4</b>	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *)Front, Rear			*)Front, Rear	400	58	550	80	550	80
<b>8 wheels</b>	710/45-26.5/24	Front, Rear		Front, Rear				400	58	550	80	600	87
	710/45R26.5				Front, Rear			400	58	550	80	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear				400	58	550	80	550	80
<b>860.4</b>	710/45-26.5/20	Rear	Rear	Rear, *)Rear			*)Rear			550	80	550	80
	710/45-26.5/24	Rear		Rear						600	87	600	87
	710/45R26.5				Rear					550	80	550	80
	800/40-26.5/20	Rear	Rear	Rear						550	80	550	80
	600/65R34				Front			320	46			400	58
	600/65-34/20						*)Front	320	46			360	52
	710/55R34				Front			320	46			400	58
700/55-34/20						*)Front	320	46			360	52	
<b>865</b>	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *)Front, Rear			*)Front, Rear	400	58	550	80	550	80
	710/45-26.5/24	Front, Rear		Front, Rear				400	58	600	87	600	87
	710/45R26.5				Front, Rear			400	58	550	80	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear				400	58	550	80	550	80
<b>865</b>	710/45-26.5/20	Rear	Rear	Rear, *)Rear			*)Rear			550	80	550	80
	710/45-26.5/24	Rear		Rear						600	87	600	87
	710/45R26.5				Rear					550	80	550	80
	800/40-26.5/20			Rear						500	73	500	73
	600/65R34				Front			360	52			400	58
	600/65-34/20						*)Front	360	52			360	52
	710/55R34				Front			340	49			400	58
700/55-34/20						*)Front	340	49			360	52	
<b>890.3</b>	750/55-26.5/20			Front, Rear			Front, Rear	450	65	550	80	550	80
	750/55-26.5/24	Front, Rear	Front, Rear					450	65	600	87	600	87
	780/55-26.5/20			Front, Rear				450	65	550	80	550	80
	800/50R26.5				Front, Rear			450	65	550	80	550	80
<b>890.3</b>	750/55-26.5/20			Rear, *)Rear			Rear, *)Rear			550	80	550	80
	750/55-26.5/24	Rear	Rear							600	87	600	87
	780/55-26.5/20			Rear						550	80	550	80
	800/50R26.5				Rear					550	80	550	80
	700/70-34/16						Front	260	38			260	38
	700/70-34/20						*)Front	320	46			360	52
710/70R34				Front			320	46			400	58	
<b>895</b>	780/50-28.5/24	Front, Rear	Front, Rear					450	65	600	87	600	87
<b>895</b>	780/50-28.5/24	Rear	Rear							600	87	600	87
	710/70R34				Front			340	49			400	58

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.









Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

CAT

Forwarders



Machine	Tyre size / PR	Tread pattern				Inflation pressure							
						Front 		Rear		With tracks		Max inflation and track pressure 	
		F	Rider	ELS	TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>584</b> <b>6 wheels</b>	750/55-26.5/20	Rear			Rear	400	58	550	80	550	80	550	80
	780/55-26.5/20	Rear				400	58	550	80	550	80	550	80
	800/50R26.5		Rear			400	58	550	80	550	80	550	80
	700/70-34/16				Front	260	41			280	41	260	41
<b>584</b> <b>8 wheels</b>	750/55-26.5/20	Front,Rear			Front,Rear	400	58	550	80	550	80	550	80
	780/55-26.5/20	Front,Rear				400	58	550	80	550	80	550	80
	800/50R26.5		Front,Rear			400	58	550	80	550	80	550	80
<b>584 HD</b> <b>8 wheels</b>	750/55-26.5/20	Front,Rear			Front,Rear	400	58	550	80	550	80	550	80
	780/55-26.5/20	Front,Rear				400	58	550	80	550	80	550	80
	800/50R26.5		Front,Rear			400	58	550	80	550	80	550	80

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

Machine	Tyre size / PR	Tread pattern						Inflation pressure				Max inflation and track pressure	
								Front		Rear			
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>1070E</b> 4 wheels	650/60-26.5/20					Front,Rear	Front,Rear	450	65	300	44	550	80
	750/55-26.5/20			Front,Rear )Front, Rear			Front,Rear )Front, Rear	450	65	300	44	550	80
	750/55-26.5/24	Front,Rear	Front,Rear					450	65	300	44	600	87
	600/65-34/20						)Front,Rear	320	46	280	41	360	52
	600/65R34				Front,Rear			320	46	280	41	400	58
	710/55R34				Front,Rear			320	46	280	41	400	58
700/55-34/20						)Front,Rear	320	46	280	41	360	52	
<b>1070E</b> 6 wheels	600/50-22.5/16					Front		400	58			430	62
	710/40-22.5/16			Front				400	58			400	58
	710/40-22.5/20	Front	Front					400	58			550	80
	650/60-26.5/12						Rear			280	41	280	41
	650/60-26.5/20					Rear	Rear			300	44	550	80
	750/55-26.5/20	Rear		Rear			Rear			300	44	550	80
	600/65-34/20						)Rear			280	41	360	52
	600/65R34				Rear					280	41	400	58
710/55-34/20						)Rear			280	41	360	52	
710/55R34				Rear					280	41	400	58	
<b>1170E</b> 6 wheels	600/50R24.5				Front			450	65			550	80
	650/45R24.5				Front			450	65			550	80
	710/40-24.5/20	Front	Front	Front, )Front				450	65			550	80
	600/65-34/20						)Rear			300	44	360	52
	600/65R34				Rear					300	44	400	58
	700/55-34/20						)Rear			300	44	360	52
710/55R34				Rear					300	44	400	58	
<b>1270E</b> 6 wheels	600/55-26.5/20	Front	Front	Front, )Front	Front		)Front	500	73			550	80
	710/45-26.5/20	Front	Front	Front, )Front	Front		)Front	500	73			550	80
	710/45-26.5/24	Front		Front				500	73			600	87
	800/40-26.5/20	Front	Front	Front				500	73			500	73
	600/65-34/20						)Rear			300	44	360	52
	600/65R34				Rear					300	44	400	58
	710/55R34				Rear					300	44	400	58
700/55-34/20						)Rear			300	44	360	52	
<b>1270E</b> 8 wheels	600/55-26.5/20	Front,Rear	Front,Rear	Front,Rear )Front, Rear	Front,Rear		)Front,Rear	500	73	400	58	550	80
	710/45-26.5/20	Front,Rear	Front,Rear	Front,Rear )Front, Rear	Front,Rear			500	73	400	58	550	80
	710/45-26.5/24	Front,Rear		Front,Rear				500	73	400	58	600	87
	800/40-26.5/20	Front,Rear	Front,Rear	Front,Rear				500	73	400	58	500	73
<b>1470E</b> 6 wheels	650/65-26.5/20					Front	Front	500	73			550	80
	750/55-26.5/20			Front, )Front			Front, )Front	500	73			550	80
	750/55-26.5/24	Front	Front					500	73			600	87
	780/55-26.5/20			Front				500	73			600	87
	710/55-28.5/24	Front	Front	Front				500	73			600	87
	780/50-28.5/24	Front	Front					500	73			600	87
	700/70-34/16						Rear			260	38	260	38
	700/70-34/20						)Rear			300	44	360	52
710/70R34				Rear					300	44	400	58	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i.

JOHN DEERE

Forwarders



Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>810E</b> 8 wheels	600/50-22.5/20						300	44	500	73	550	80
	710/40-22.5/16			Front, Rear			300	44	400	58	400	58
	710/40-22.5/20	Front,Rear	Front,Rear				300	44	500	73	550	80
<b>1010E</b> 6 wheels	600/50R24.5				Rear				550	80	550	80
	650/45R24.5				Rear				550	80	550	80
	710/40-24.5/20	Rear	Rear	Rear					500	73	550	80
	600/65-34/20					*)Front	300	44			360	52
	600/65R34				Front		300	44			400	58
	700/55-34/20					*)Front	300	44			360	52
	710/55R34				Front		300	44			400	58
28L-26/26					Front	300	44			420	61	
<b>1010E</b> 8 wheels	600/50R24.5				Front,Rear		400	58	550	80	550	80
	650/45R24.5				Front,Rear		400	58	550	80	550	80
	710/40-24.5/20	Front,Rear	Front,Rear	Front, Rear			400	58	500	73	550	80
<b>1110E</b> 8 wheels	600/55-26.5/20	Front,Rear	Front,Rear	Front, Rear *) Front, Rear		*)Front,Rear	400	58	550	80	550	80
	600/55R26.5				Front,Rear		400	58	550	80	550	80
	710/45-26.5/20	Front,Rear	Front,Rear	Front, Rear *) Front, Rear		*) Front, Rear	400	58	500	73	550	80
	710/45-26.5/24	Front,Rear		Front, Rear			400	58	500	73	600	87
	710/45R26.5				Front,Rear		400	58	500	73	550	80
	800/40-26.5/20	Front, Rear	Front,Rear	Front, Rear			400	58	500	73	500	73
<b>1110E</b> 6 wheels	600/55-26.5/20	Rear	Rear	Rear		*)Rear			550	80	550	80
	600/55R26.5				Rear				550	80	550	80
	710/45-26.5/20	Rear	Rear	Rear					500	73	550	80
	710/45-26.5/24	Rear		Rear					500	73	550	80
	710/45R26.5				Rear				500	73	550	80
	800/40-26.5/20			Rear					500	73	500	73
	600/65-34/20					*)Front	300	44			360	52
	600/65R34				Front		300	44			400	58
	710/55R34				Front		300	44			400	58
700/55-34/20					*)Front	300	44			360	52	
28L-26/26					Front	300	44			420	61	
<b>1210E</b> 8 wheels	600/55-26.5/20	Front,Rear	Front,Rear	Front, Rear *) Front, Rear		*)Front,Rear	400	58	550	80	550	80
	600/55R26.5				Front, Rear		400	58	550	80	550	80
	710/45-26.5/20	Front,Rear	Front,Rear	Front, Rear *) Front, Rear		*)Front,Rear	400	58	500	73	550	80
	710/45-26.5/24	Front,Rear		Front, Rear			400	58	500	73	600	87
	710/45R26.5				Front, Rear		400	58	500	73	550	80
	800/40-26.5/20	Front,Rear	Front,Rear	Front, Rear			400	58	500	73	550	80

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

**JOHN DEERE**

Forwarders









Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>1210E</b> 6 wheels	600/55-26.5/20	Rear	Rear	Rear					550	80	550	80
	600/55R26.5				Rear				550	80	550	80
	710/45-26.5/20	Rear	Rear	Rear					500	73	550	80
	710/45-26.5/24	Rear		Rear					500	73	600	87
	710/45R26.5				Rear				500	73	550	80
	800/40-26.5/20			Rear					500	73	500	73
	600/65-34/20					)Front	300	44			360	52
	600/65R34				Front		300	44			400	58
	710/55R34				Front		300	44			400	58
700/55-34/20					)Front	300	44			360	52	
28L-26/16					Front	300	44			420	61	
<b>1510E</b> 8 wheels	710/45-26.5/20	Front,Rear	Front,Rear	Front, Rear			400	58	550	80	550	80
	710/45-26.5/24	Front,Rear		Front, Rear			400	58	600	87	600	87
	710/45R26.5				Front,Rear		400	58	550	80	550	80
	800/40-26.5/20	Front,Rear	Front,Rear	Front, Rear			400	58	550	80	550	80
<b>1510E</b> 6 wheels	710/45-26.5/20	Rear	Rear	Rear					550	80	550	80
	710/45-26.5/24	Rear		Rear					600	87	600	87
	710/45R26.5				Rear				550	80	550	80
	800/40-26.5/20		Rear	Rear					500	73	500	73
	600/65R34				Front		320	46			400	58
	600/65-34/20					)Front	320	46			360	52
	710/55R34				Front		320	46			400	58
700/55-34/20					)Front	320	46			360	52	
<b>1910E</b> 8 wheels	750/55-26.5/20			Front,Rear )Front, Rear					550	80	550	80
	750/55-26.5/24	Front,Rear	Front,Rear				450	65	600	87	600	87
	780/55-26.5/20			Front,Rear			450	65	600	87	600	87
	800/50R26.5				Front,Rear		450	65	550	80	550	80
	780/50-28.5/24	Front,Rear	Front,Rear				450	65	600	87	600	87
<b>1910E</b> 6 wheels	750/55-26.5/20			Rear, )Rear					550	80	550	80
	750/55-26.5/24	Rear	Rear						600	87	600	87
	780/55-26.5/20			Rear					600	87	600	87
	800/50R26.5				Rear				550	80	550	80
	780/50-28.5/24	Rear	Rear						600	87	600	87
	700/70-34/16					Front	260	38			260	38
	700/70-34/20					)Front	340	49			360	52
710/70R34				Front		340	49			400	58	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i



Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front 		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>4H</b> 4 wheels	650/60-26.5/12					Front,Rear	240	35	240	35	280	41
	750/55-26.5/20			Front,Rear, ) Front, Rear		Front, Rear, ) Front, Rear	280	41	280	41	550	80
	750/55-26.5/24	Front,Rear	Front,Rear				280	41	280	41	550	80
	780/55-26.5/20			Front,Rear			280	41	280	41	550	80
	600/65-34/20					) Front,Rear	280	41	280	41	360	52
	600/65R34				Front,Rear		280	41	280	41	400	58
	700/55-34/20					) Front,Rear	260	38	280	41	360	52
	710/55R34				Front,Rear		260	38	280	41	400	58
<b>5H</b> 6 wheels	600/50-22.5/20					Front	430	62			550	80
	710/40-22.5/16			Front			400	58			430	62
	710/40-22.5/20	Front	Rear	Front			400	58			550	80
	600/65-34/20					) Rear			280	41	360	52
	600/65R34				Rear				280	41	400	58
	700/55-34/20					) Rear			280	41	360	52
	710/55R34				Rear			280	41	400	58	
<b>6H</b> 6 wheels	600/55-26.5/20	Front	Front	Front, *)Front		) Front	550	80			550	80
	600/55R26.5				Front		550	80			550	80
	710/45-26.5/20	Front	Front	Front, *)Front		) Front	550	80			550	80
	710/45R26.5				Front		550	80			550	80
	800/40-26.5/20	Front	Front	Front			550	80			550	80
	600/65-34/20					) Rear			280	41	360	52
	600/65R34				Rear				280	41	400	58
	700/55-34/20					) Rear			280	41	360	52
	710/55R34				Rear			280	41	400	58	
<b>8H</b> 6 wheels	600/55-26.5/20	Front	Front	Front, *) Front		) Front	550	80			550	80
	600/55R26.5				Front		550	80			550	80
	710/45-26.5/20	Front	Front	Front, *) Front		) Front	550	80			550	80
	710/45R26.5				Front		550	80			550	80
	800/40-26.5/20	Front	Front	Front			550	80			550	80
	600/65-34/20					) Rear			280	41	360	52
	600/65R34				Rear				280	41	400	58
	700/55-34/20					) Rear			280	41	360	52
	710/55R34				Rear			280	41	400	58	
<b>10H</b> 6 wheels	750/55-26.5/20			Front, *)Front		Front, *) Front	500	73			550	80
	750/55-26.5/24	Front	Front				500	73			550	80
	780/55-26.5/20			Front			500	73			550	80
	710/55-28.5/24	Front	Front				500	73			600	87
	780/50-28.5/24	Front	Front				500	73			600	87
	700/70-34/16					Rear			260	38	260	38
	700/70-34/20					)Rear			300	44	360	52
	710/70R34				Rear			300	44	400	58	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.








Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

**LOGSET**

Forwarders

**LOGSET**

Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	Front		Rear			
							kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>4F</b> 8 wheels	600/50-22.5/20					Front, Rear	350	51	500	73	550	80
	710/40-22.5/16			Front, Rear			350	51	430	62	430	62
	710/40-22.5/20	Front, Rear	Front, Rear				350	51	430	62	430	62
<b>5F</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear		*) Front, Rear	350	51	550	80	550	80
	600/55R26.5				Front, Rear		350	51	550	80	550	80
	710/45-26.5/16			Front, Rear			350	51	460	67	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear		*) Front, Rear	350	51	500	73	550	80
	710/45R26.5				Front, Rear		350	51	500	73	550	80
800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			350	51	500	73	550	80	
<b>6F</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear		*) Front, Rear	350	51	550	80	550	80
	600/55R26.5				Front, Rear		350	51	550	80	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear		*) Front, Rear	350	51	550	80	550	80
	710/45R26.5				Front, Rear		350	51	550	80	550	80
<b>8F</b> 8 wheels	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *) Front, Rear		*) Front, Rear	400	58	550	80	550	80
	710/45-26.5/24	Front, Rear			Front, Rear		400	58	550	80	600	87
	710/45R26.5				Front, Rear		400	58	550	80	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			400	58	500	73	550	80
<b>10F</b> 8 wheels	750/55-26.5/20			Front, Rear, *) Front, Rear		Front, Rear, *) Front, Rear	400	58	550	80	550	80
	750/55-26.5/24	Front, Rear	Front, Rear				400	58	550	80	600	87
	780/55-26.5/20			Front, Rear			400	58	550	80	550	80
	780/50-28.5/24	Front, Rear	Front, Rear				400	58	600	87	600	87

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

**PONSSE**  
Harvester



Machine	Tyre size / PR	Tread pattern						Inflation pressure				Max inflation and track pressure	
								Front		Rear			
		F2	TRS 2	F Nordman F	Rider	ELS	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>Beaver</b> 6 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear )Front, Rear	Front,Rear		)Front, Rear	380	55	460	67	550	80
	600/55R26.5				Front,Rear			380	55	460	67	550	80
	710/45-26.5/16			Front,Rear				350	51	460	67	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear )Front, Rear			)Front, Rear	350	51	460	67	550	80
	710/45R26.5				Front,Rear			350	51	460	67	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	460	67	550	80
	650/65-26.5/20			Front,Rear		Front	Front	350	51	460	67	550	80
750/55-26.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	460	67	550	80	
<b>Fox</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front,Rear )Front, Rear			)Front, Rear	400	58	460	67	550	80
	600/55R26.5				Front,Rear			400	58	460	67	550	80
	710/45-26.5/16			Front,Rear				400	58	460	67	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear ) Front, Rear			)Front, Rear	400	58	460	67	550	80
	710/45R26.5				Front,Rear			400	58	460	67	550	80
	800/40-26.5	Front, Rear	Front, Rear	Front,Rear				400	58	460	67	550	80
<b>Scorpion</b> Scorpion King 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front,Rear )Front, Rear			)Front, Rear	450	65	450	65	550	80
	600/55R26.5				Front,Rear			450	65	450	65	550	80
	710/45-26.5/16			Front,Rear				450	65	450	65	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear )Front, Rear			)Front, Rear	450	65	450	65	550	80
	710/45R26.5				Front,Rear			450	65	450	65	550	80
800/40-26.5	Front, Rear	Front, Rear	Front,Rear				450	65	450	65	550	80	
<b>Ergo</b> 6 wheels	600/55-26.5/20	Rear		Rear, *)Rear			)Rear			460	67	550	80
	600/55R26.5				Rear					460	67	550	80
	710/45-26.5/16			Rear						460	67	460	67
	710/45-26.5/20	Rear		Rear, *) Rear			)Rear			460	67	550	80
	710/45R26.5				Rear					460	67	550	80
	800/40-26.5/20	Rear	Rear	Rear						460	67	550	80
	600/65-34/20						)Front	300	44			360	52
	600/65R34				Front			300	44			400	58
	700/55-34/20						)Front	300	44			360	52
710/55R34				Front			300	44			400	58	
<b>Ergo</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front,Rear ) Front, Rear			)Front, Rear	350	51	460	67	550	80
	600/55R26.5				Front,Rear			350	51	460	67	550	80
	710/45-26.5/16			Front,Rear				350	51	460	67	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear ) Front, Rear			)Front, Rear	350	51	460	67	550	80
	710/45R26.5				Front,Rear			350	51	460	67	550	80
	800/40-26.5	Front, Rear	Front, Rear	Front,Rear				350	51	460	67	550	80

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating: 250 kPa / 36 p.s.i

**PONSSE**  
Harvester



Machine	Tyre size / PR	Tread pattern						Inflation pressure					
		F2	TRS 2	F	Rider	ELS	TRS	Front		Rear		Max inflation and track pressure	
				(* Nordman F)			(* Nordman TRS)	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>Bear</b> <b>8 wheels</b>	650/65-26.5/20					Front,Rear	Front,Rear	400	58	460	67	550	80
	750/55-26.5/20			Front,Rear, (*)Front,Rear			Front,Rear, (*)Front,Rear	400	58	460	67	550	80
	750/55-26.5/24	Front, Rear	Front, Rear					400	58	460	67	600	87
	780/55-26.5/20			Front,Rear				400	58	460	67	550	80
	800/50R26.5			Front,Rear				400	58	460	67	550	80
	710/55-28.5/24	Front, Rear	Front, Rear					400	58	460	67	600	80
	780/50-28.5/24	Front, Rear	Front, Rear					400	58	460	67	600	80
<b>Bear</b> <b>6 wheels</b>	650/65-26.5/20					Rear	Rear			460	67	550	80
	750/55-26.5/20			Rear, (*)Rear			Rear, (*)Rear			460	67	550	80
	750/55-26.5/24	Rear	Rear							460	67	600	87
	780/55-26.5/20			Rear						460	67	550	80
	710/55-28.5/24	Rear	Rear							460	67	600	87
	780/50-28.5/24	Rear	Rear							460	67	600	87
	800/50R26.5			Rear						460	67	550	80
	700/70-34/16						Front	260	38			260	38
	700/70-34/20						Front	300	44			360	52
710/70R34				Front			300	44			400	58	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

**PONSSE**  
Forwarders



Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>Gazelle</b> 8 wheels	600/50-22.5/20					Front,Rear	350	51	500	73	550	80
	710/40-22.5/16			Front,Rear		Front,Rear	350	51	430	62	430	62
	710/40-22.5/20	Front,Rear	Front,Rear				350	51	430	62	430	62
<b>Wisent / Dual</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front,Rear, )Front, Rear		)Front,Rear	350	51	550	80	550	80
	600/55R26.5				Front,Rear		350	51	550	80	550	80
	710/45-26.5/16			Front,Rear			350	51	460	67	460	67
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear, )Front, Rear		)Front,Rear	350	51	500	73	550	80
	710/45R26.5				Front,Rear		350	51	500	73	550	80
800/40-26.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	500	73	500	73
<b>Wisent / Dual</b> 6 wheels	600/55-26.5/20	Rear	Rear	Rear, *)Rear		)Rear			550	80	550	80
	600/55R26.5				Rear				550	80	550	80
	710/45-26.5/16			Rear					460	67	460	67
	710/45-26.5/20	Rear	Rear	Rear, *)Rear		)Rear			500	73	550	80
	710/45R26.5				Rear				500	73	550	80
	800/40-26.5/20	Rear	Rear	Rear					500	73	550	80
	600/65-34/20					)Front	300	44			360	52
	600/65R34				Front		300	44			400	58
700/55-34/20					)Front	300	44			360	52	
710/55R34				Front		300	44			400	58	
<b>Elk</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front,Rear, )Front, Rear		)Front,Rear	350	51	550	80	550	80
	600/55R26.5				Front,Rear		350	51	550	80	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front,Rear, )Front, Rear		)Front,Rear	350	51	500	73	550	80
	710/45-26.5/24	Front, Rear		Front,Rear			350	51	500	73	600	87
	710/45R26.5				Front,Rear		350	51	500	73	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front,Rear				350	51	500	73	550
<b>Elk</b> 6 wheels	600/55-26.5/20	Rear	Rear	Rear, *)Rear		)Rear			550	80	550	80
	600/55R26.5				Rear				550	80	550	80
	710/45-26.5/20	Rear	Rear	Rear, *)Rear		)Rear			500	73	550	80
	710/45-26.5/24	Rear		Rear					500	73	600	87
	710/45R26.5				Rear				500	73	550	80
	800/40-26.5/20	Rear	Rear	Rear					500	73	550	80
	600/65-34/20					)Front	320	46			360	52
	600/65R34				Front		320	46			400	58
700/55-34/20					)Front	320	46			360	52	
710/55R34				Front		320	46			400	58	

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

**PONSSE**

Forwarders



Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>Buffalo / Dual 8 wheels</b>	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, *)Front, Rear		*)Front, Rear	400	58	550	80	550	80
	710/45-26.5/24	Front, Rear		Front, Rear			400	58	550	80	600	87
	710/45R26.5				Front, Rear		400	58	550	80	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			400	58	550	80	550	80
<b>Buffalo / Dual / ADS 6 wheels</b>	710/45-26.5/20	Rear	Rear	Rear, *)Rear		*)Rear			550	80	550	80
	710/45-26.5/24	Rear		Rear					550	80	600	87
	710/45R26.5				Rear				550	80	550	80
	800/40-26.5/20	Rear	Rear	Rear					550	80	550	80
	600/65-34/20					*)Front	320	46			360	52
	600/65R34				Front		320	46			400	58
	700/55-34/20					*)Front	320	46			360	52
710/55R34				Front		320	46			400	58	
<b>Buffalo King 8 wheels</b>	600/55-26.5/20	Front	Front	Front, *)Front		*)Front	400	58			550	80
	600/55R26.5				Front		400	58			550	80
	710/45-26.5/20	Front	Front	Front, *)Front		*)Front	400	58			550	80
	710/45-26.5/24	Front		Front			400	58			600	87
	710/45R26.5				Front		400	58			550	80
	800/40-26.5/20	Front	Front	Front			400	58			550	80
	750/55-26.5/20			Rear, *)Rear		Rear, *)Rear			550	80	550	80
	750/55-26.5/24	Rear	Rear						550	80	600	87
780/55-26.5/20			Rear					550	80	550	80	
800/50R26.5				Rear				550	80	550	80	
<b>Buffalo King 6 wheels</b>	750/55-26.5/20			Rear, *)Rear		Rear, *)Rear			500	73	550	80
	750/55-26.5/24	Rear	Rear						500	73	600	87
	780/55-26.5/20			Rear					500	73	550	80
	800/50R26.5				Rear				500	73	550	80
	700/70-34/16					Front	260	38			260	38
	700/70-34/20					*)Front	300	44			360	52
	710/70R34				Front		300	44			400	58
<b>Elephant 8 wheels</b>	750/55-26.5/20			Front, Rear *)Front, Rear		Front, Rear *)Front, Rear	450	65	550	80	550	80
	750/55-26.5/24	Front, Rear	Front, Rear				450	65	600	87	600	87
	780/55-26.5/20			Front, Rear			450	65	550	80	550	80
	780/50-28.5/24	Front, Rear	Front, Rear				450	65	600	87	600	87
	800/50R26.5				Front, Rear		450	65	550	80	550	80
<b>Elephant 6 wheels</b>	750/55-26.5/20			Rear, *)Rear		Rear, *)Rear			550	80	550	80
	750/55-26.5/24	Rear	Rear						600	87	600	87
	780/55-26.5/20			Rear					550	80	550	80
	800/50R26.5				Rear				550	80	550	80
	780/50-28.5/24	Rear	Rear						600	87	600	87
	700/70-34/16					Front	260	38			260	38
	700/70-34/20					*)Front	320	46			360	52
	710/70R34				Front		320	46			400	58
<b>Elephant King 8 wheels</b>	750/55-26.5/20			Front, Rear *)Front, Rear		Front, Rear *)Front, Rear	450	65	550	80	550	80
	750/55-26.5/24	Front, Rear	Front, Rear				450	65	600	87	600	87
	780/55-26.5/20			Front, Rear			450	65	550	80	550	80
	780/50-28.5/24	Front, Rear	Front, Rear				450	65	600	87	600	87
	800/50R26.5				Front, Rear		450	65	550	80	550	80

Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>H8</b> 4 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, ) Front, Rear		) Front, Rear	450	65	450	65	550	80
	600/55R26.5				Front, Rear		450	65	450	65	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear, ) Front, Rear		) Front, Rear	450	65	450	65	550	80
	710/45R26.5				Front, Rear		450	65	450	65	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			450	65	450	65	550	80
<b>H11</b> 6 wheels	600/50R24.5				Front		500	73			550	80
	650/45R24.5				Front		500	73			550	80
	710/40-24.5	Front	Front	Front, *) Front			500	73			550	80
	600/65-34/20					) Rear			280	41	360	52
	600/65R34				Rear				280	41	400	58
	700/55-34/20					) Rear			280	41	360	52
710/55R34				Rear				280	41	400	58	
<b>H11c</b> 8 wheels	600/50R24.5				Front, Rear		500	73	450	65	550	80
	650/45R24.5				Front, Rear		500	73	450	65	550	80
	710/40-24.5	Front, Rear	Front, Rear	Front, Rear, ) Front, Rear			500	73	450	65	550	80
<b>H14c</b> 6 wheels	600/55-26.5/20	Front	Front	Front, *) Front		) Front	500	73			550	80
	600/55R26.5				Front		500	73			550	80
	710/45-26.5/20	Front	Front	Front, *) Front		) Front	500	73			550	80
	710/45R26.5				Front		500	73			550	80
	800/40-26.5/20	Front	Front	Front			500	73			550	80
	600/65-34/20					) Rear			280	41	360	52
	600/65R34				Rear				280	41	400	58
	700/55-34/20					) Rear			280	41	360	52
710/55R34				Rear				280	41	400	58	
<b>H20b</b> 6 wheels	750/55-26.5/20			Front, *) Front		) Front	500	73			550	80
	750/55-26.5/24	Front	Front				500	73			550	80
	780/55-26.5/20			Front			500	73			550	80
	700/70-34/16					Rear			260	38	260	38
	700/70-34/20					Rear			300	44	360	52
	710/70R34				Rear				300	44	400	58
<b>H21d</b> 8 wheels	750/55-26.5/20			Front, Rear ) Front, Rear		) Front, Rear	500	73	450	65	550	80
	750/55-26.5/24	Front, Rear	Front, Rear				500	73	450	65	600	87
	780/55-26.5/20			Front			500	73	450	65	550	80
<b>H21d</b> 6 wheels	750/55-26.5/20			Front, Rear ) Front, Rear		) Front, Rear	500	73	450	65	550	80
	750/55-26.5/24	Front, Rear	Front, Rear				500	73	450	65	600	87
	780/55-26.5/20			Front			500	73	450	65	550	80
	700/70-34/16					Rear			260	38	260	38
	700/70-34/20					Rear			300	44	360	52
	710/70R34				Rear				300	44	400	58

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i

Machine	Tyre size / PR	Tread pattern					Inflation pressure				Max inflation and track pressure kPa p.s.i.	
							Front		Rear			
		F2	TRS 2	F Nordman F	Rider	TRS Nordman TRS	kPa	p.s.i.	kPa	p.s.i.	kPa	p.s.i.
<b>F10b</b> 8 wheels	600/50-22.5/20					Front, Rear	350	51	500	73	550	80
	710/40-22.5/16			Front, Rear		Front, Rear	350	51	400	58	430	62
	710/40-22.5/20	Front, Rear	Front, Rear				350	51	500	73	550	80
<b>F13c</b> 8 wheels	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear, ) Front, Rear		) Front, Rear	350	51	550	80	550	80
	600/55R26.5				Front, Rear		350	51	550	80	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear ) Front, Rear		) Front, Rear	350	51	500	73	550	80
	710/45R26.5				Front, Rear		350	51	500	73	550	80
<b>F15c</b> 8 wheels	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			350	51	500	73	550	80
	600/55-26.5/20	Front, Rear	Front, Rear	Front, Rear ) Front, Rear		) Front, Rear	450	65	550	80	550	80
	600/55R26.5				Front, Rear		450	65	550	80	550	80
	710/45-26.5/20	Front, Rear	Front, Rear	Front, Rear ) Front, Rear		) Front, Rear	400	58	550	80	550	80
<b>F18</b> 6 wheels	710/45R26.5				Front, Rear		400	58	550	80	550	80
	710/70R34				Front, Rear		400	58	550	80	550	80
	800/40-26.5/20	Front, Rear	Front, Rear	Front, Rear			400	58	550	80	550	80
	750/55-26.5/20			Rear, *) Rear		Rear, *) Rear			550	80	550	80
	750/55-26.5/24	Rear	Rear						600	87	600	87
<b>F18</b> 8 wheels	780/55-26.5/20			Rear					550	80	550	80
	710/70-34/16					Front	260	38			260	38
	710/70-34/20					) Front	320	46			360	52
	710/70R34				Front		320	46			400	58
	750/55-26.5/20			Front, Rear, ) Front, Rear		Front, Rear, ) Front, Rear	450	65	550	80	550	80
<b>F18</b> 8 wheels	750/55-26.5/24	Front, Rear	Front, Rear				450	65	600	87	600	87
	780/55-26.5/20			Front, Rear			450	65	550	80	550	80

\*) For safety reasons, the original equipment (OE) delivery inflation pressures are lower than the application recommendations.



Maximum inflation pressure in bead seating:  
250 kPa / 36 p.s.i